

波纹特氟龙软管 PC



应用：

- 适用于制药、食品、化工、饮料等，几乎可以应用在任何行业

优点：

- 里层为波纹状的PTFE 软管，外覆SS304 不锈钢编织
- 质轻，非常柔软，易清洗，易排水，应用范围非常广
- 标准与防静电内衬可供选择

温度范围：

- -70℃至+260℃

认证标准：

- 符合FDA认证

Applications:

- For pharmaceutical, food, chemical, beverage and an almost endless list of applications

Advantages:

- Lightweight, highly flexible, convoluted PTFE hose, with 304 stainless steel over braid
- Low profile liner self-draining, easy clean solution for a wide range of applications
- Virgin and anti-static liners available

Temperature:

- -70 °C to +260 °C

Standard/Approval:

- FDA

波纹特氟龙软管 PC

产品编码 No.	内径 in	mm	内管壁厚 mm	外径 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm
PC-0250	1/4"	7.1	0.8	12.3	172	517	18
PC-0380	3/8"	9.5	0.8	15.25	138	414	20
PC-0500	1/2"	12.8	0.9	18.8	103	310	25
PC-0630	5/8"	15.9	0.9	22.1	83	248	51
PC-0750	3/4"	19.1	0.9	24.7	69	207	64
PC-0870	7/8"	22.4	0.9	28.7	57	172	76
PC-1000	1"	25.4	1.0	32.8	46	138	89
PC-1250	1-1/4"	32.2	1.0	40.7	34	103	127
PC-1500	1-1/2"	38.1	1.1	48.3	30	90	152
PC-2000	2"	51.4	1.2	61.5	23	69	200

